













Artículo / Item / Article	Imagen / Picture / Image	Medidas / Size / Dimensions (mm)							Material / Matière				
		Longitud (sin pestaña) / Length (without flange) / Longueur (sans rebord)	Longitud (con pestaña) / Length (with flange) / Longueur (avec rebord)	Anchura (sin pestaña) / Width (without flange) / Largeur (sans rebord)	Anchura (con pestaña) / Width (with flange) / Largeur (avec rebord)	Altura / Height / Hauteur	Espacio chapado / Tile space / Épaisseur à carreler	Salida / Drain / Écoulement \varnothing	Rejilla / Grate / Grille	Base	Salida / Drain / Écoulement	Sifón / Siphon	Filtro / Strainer / Filtre
CANALETA LÍNEAS 600		600	640	70	110	67	15	40	SUS304	SUS304	SUS304	ABS	ABS
CANALETA LÍNEAS 700		700	740	70	110	67	15	40	SUS304	SUS304	SUS304	ABS	ABS
CANALETA LÍNEAS 800		800	840	70	110	67	15	40	SUS304	SUS304	SUS304	ABS	ABS
CANALETA OLAS 600		600	640	70	110	67	15	40	SUS304	SUS304	SUS304	ABS	ABS
CANALETA OLAS 700		700	740	70	110	67	15	40	SUS304	SUS304	SUS304	ABS	ABS
CANALETA OLAS 800		800	840	70	110	67	15	40	SUS304	SUS304	SUS304	ABS	ABS
CANALETA PUNTOS 600		600	640	70	110	67	15	40	SUS304	SUS304	SUS304	ABS	ABS
CANALETA PUNTOS 700		700	740	70	110	67	15	40	SUS304	SUS304	SUS304	ABS	ABS
CANALETA PUNTOS 800		800	840	70	110	67	15	40	SUS304	SUS304	SUS304	ABS	ABS
DESAGÜE CUADRADO LÍNEAS		150	190	150	190	67	15	40	SUS304	SUS304	SUS304	ABS	ABS
DESAGÜE CUADRADO OLAS		150	190	150	190	67	15	40	SUS304	SUS304	SUS304	ABS	ABS
DESAGÜE CUADRADO SOL		150	190	150	190	67	15	40	SUS304	SUS304	SUS304	ABS	ABS

Salida DN40 con adaptador de DN40 a DN 50

Capacidad de flujo 25 L/M

Accesorios incluidos: patas ajustables, adaptador DN40-DN50, filtro, membrana impermeable, sifón y gancho de limpieza

Drain DN40 with DN40 to DN 50 adaptor

Flow capacity: 25 L/M

Included accessories: adjustable legs, DN40-DN50 adaptor, strainer, waterproof membrane, siphon and hook.

Sortie DN40 avec adaptateur DN50

Capacité de flux: 25 L/M

Accessoires inclus: Pieds ajustables, adaptateur DN40-dn50, crépine, toile étanche, siphon et crochet.